

## Glass Chiller Remote

### Features:

- Designed for 43°C ambient environment
- Adjustable electronic controller with digital temperature display
- Forced air refrigeration system
- Fitted with evaporator, TX valve, controller, fitted plug, junction box and condensate drain
- 100% CFC free polyurethane foam for greater insulation properties and added strength
- Spring loaded lifting mechanism or adjustable shelves accommodates 355mm x 355mm or 355mm x 431mm baskets
- Shelf model fitted with two plastic coated shelves per door
- Refrigerant pipes exit thru left hand end as standard
- Self closing doors with easy to clean handles
- On castors for mobility – legs are supplied with cabinet
- Face mounted hinges (plinth mount ready)
- Polycarbonate night lid
- Drain thru floor for clean out

## Glass Chiller



MODEL	GC1R	GC2R
Capacity – Baskets (not included)	4	8
<b>Finish: Stainless steel interior &amp; exterior*</b>		
Refrigerator Glass Door Spring Loaded +1°/+4° kg-unpacked / Amps-run / Wr-refrigeration Watts (nom.)	<b>GC1RSL</b> 60/0.4/570	<b>GC2RSL</b> 100/0.5/750
<b>Finish: Stainless steel interior &amp; exterior*</b>		
Refrigerator Glass Door Adjustable shelf configuration +1°/+4° kg-unpacked / Amps-run / Wr-refrigeration Watts (nom.)	<b>GC1R</b> 60/0.4/570	<b>GC2R</b> 100/0.5/750

\*Refer notes page 35

Gas: Remote units R404a (others available)  
Electrical lead length 1.5m min. 240V 50Hz

Options (see page 35):

