




MiClean HM


Commercial Pass Through Dishwasher











Product Features & Benefits

- Automatic hood operation with basket detection as standard. Hood closes once wash basket enters the machine and opens at the end of cycle.
- Touch TFT colour display made from hygienic safety glass with program progress indicator and Bluetooth interface that can be mounted on the left or right of hood or elsewhere in the wash area.
- Intuitive operation-blue operating concept, components that need checking after self-clean cycle are blue in colour
- M-Clean filter-active filter system for removal of food debris from wash tank (includes monitoring of correct positioning and function)
- Stainless steel detergent and rinse aid lines with in the body of the machine
- Stainless steel single piece wash and rinse arms to improve wash result.
- Stainless steel wash and rinse manifold for longevity and reliability.

TECHNICAL SPECIFICATIONS Basket dimensions in mm 500 x 500 60/90/210 #Programme cycle in seconds #Theoretical basket capacity 60/40/17 Water consumption liters per cycle 2.4 Variable Machine 1.0 Pump out drain Hose ¾ " connection drain pipe Max. 750mm 1.1 Drain point 50mm from floor Machine 2.0 Thread ¾ " Nominal value connection water point 1 bar -5 bar Water supply Flow pressure 2.1 point Temperature Hot Water Water hardness Max 53.4ppm Machine 5G 6mm2 supply 3.0 **Total rating** cable fitted connection electrical Electrical Three phase 3.1 3NPE 400V 50Hz, point 9.1 Kw

On cold water connection and/or shortbasket exchange times, the wash cycles may increase to achieve hygienic rinse temperatures # Cycle time can be customized to specific requirements on site

Optional Features

- GiO Reverse Osmosis
- Air Concept heat recovery system