

PROFESSIONAL STACKED DRYERS

COMMERCIAL RANGE

PSGJX (OPL) Twin Stack Dyer 2 X 10kg



FEATURES STACK UNITS

- Totally freestanding:can be instaled on any floor and any level
- Reduced floor space
- OPL 20kg capacity
- Top, front and side panels standard available in anthracite grey
- Door opens 180° for easy loading and unloading
- LED indication of the status of the program
- Time remaining countdown

FEATURES DRYERS

- Galvanized steel cylinder
- Oversized lint filter located in front for easy cleaning
- Powerful exhaust blower assures short drying times and low operating costs
- gas heating
- 4 drying programs
- LED indication of the status of the program







UNIT


EASY

TYPE	to .	DRYER
CAPACITY	kg	2 x 10
DRUM VOLUME	i j	2 x 198
MOTOR	kW	2 x 0.25
DOOR TYPE		Solid
CYLINDER FINISH		Galvanised
CYCLE INDICATOR LIGHTS		Yes
ELECTRICAL CONNECTION		2 x 1x220-240V/50Hz

TYPE		PSGJX
MODEL		dryer/dryer
HEAT SOURCE		Gas
CONTROL		10 degree front
GAS BURNER	kW	7.3
HEATING		
HEATING ELEMENT	kW	N/A
CONNECTION		
GAS INLET CONNECTION	mm	9.5
GAS CONSUMPTION	BTU/hr	25000
EXHAUST OUTLET DIAMETER	mm	102
EXHAUST AIRFLOW	l/s	2 x 60Hz: 105 (220) 50Hz: 85 (180)
OPERATION		
CYCLES		D4
TRANSPORT DATA		
NET WEIGHT	kg	120
SHIPPING WEIGHT	kg	127
DIMENSIONS H x W x D	mm	1986 x 683 x 737
PACKING DIMENSIONS H x W x D	mm	2032 x 864 x 760







PSGJX (OPL)

VISIT OUR WEBSITE www.totalce.com.au CALL US ON 1300 355 769



Complete Project Solutions™

