

# PTGJX (OPL) COMMERCIAL WASHER/DRYER STACK

Washer	Dryer
10kg	10kg



## FEATURES: STACK UNIT

- Freestanding units can be installed on any floor and any level
- Double capacity within the same footprint
- Two separate controls
- Door opens 180 degrees for easy loading and unloading
- Time remaining countdown

## FEATURES: WASHER

- 6 factory presets with cycle modifiers that offer almost unlimited flexibility
- Low water usage
- Industry-leading 440 G-Force extraction
- Suspension with new out-of-balance logic
- Stainless steel inner and outer cylinder
- Soap box with four compartments

## FEATURES: DRYER

- 4 drying programs
- Large door opening for easy loading and unloading
- Reversible door
- Front access to vital parts for easy maintenance
- Galvanized steel cylinder
- Nonremovable lint filter located in front for easy cleaning
- Powerful exhaust blower ensures short dry times and low operating costs
- gas heating



ERGONOMICAL  
CONSTRUCTION



LARGE DOOR  
OPENING



LOW WATER  
AND ENERGY  
CONSUMPTION

TYPE		PTGJX (OPL)
<b>DRAIN</b>		
Type		Stack Washer Dryer
Control		Electronic
Control location		Front
<b>DRUM</b>		
Capacity	kg	W- 10 / D-10
Cylinder volume	liters	W-96.8 / D-198
<b>DRUM SPEED</b>		
G-force		440
Spin speed	RPM	1200
<b>MOTOR</b>		
Motor power	kW	W-.67/D-.25
<b>CABINET</b>		
Cylinder finish		W-SS/D-Galvanized
Colour		Gray
Door type (solid/window)		W-Window / D-Solid
<b>HEATING</b>		
Heat source		W-NA/D-Gas
Heating power		Gas - 25000 Btu
<b>CONNECTION</b>		
Gas inlet connection	mm	9,5
Exhaust outlet diameter	mm	102
Exhaust airflow	l/sec	105
Water inlet	in	0,75
Water pressure	bar	1.4-8.3
Drain		Pump 47mm
<b>OPERATION</b>		
Cycles		W-6 / D-4
Water temperatures		3
Water consumption per cycle litres*		51,78
Cycle indicator lights		Yes
<b>POWER</b>		
Electrical requirements	voltage/ Hz/Ph	220-240/50/1
<b>TRANSPORT DATA</b>		
Net weight	kg	175
Shipping weight	kg	189
Dimensions HxWxD	mm	1986 x 683 x 704
Packing Dimensions HxWxD	mm	2032 x 864 x 762
Volume	m <sup>3</sup>	1,34
<b>AGENCY APPROVALS</b>		
Applicable approvals		QEC, Australian Gas, Water mark

VISIT OUR WEBSITE [www.totalce.com.au](http://www.totalce.com.au)  
CALL US ON **1300 355 769**

