CWC611D - EasyLine 500/600x500mm basket



- Double skin, fully insulated hood and panels
- ♦ Construction in AISI 304 stainless steel
- ♦ Small capacity tank (22lt), moulded and with rounded edges
- ♦ Hood opening height: 410mm
- ♦ Capacity to wash 600x500mm dish baskets and 600x400 trays
- 20% higher load capacity compared to standard pass-through dishwashers
- ♦ HTR (High Temperature Rinse) system with atmospheric boiler and rinse pump
- ♦ 3 litres water rinse cycle
- ♦ Drain pump
- ♦ Water connection: from Cold to 60°C
- ♦ Wash and rinse arms in stainless steel
- ♦ Full size tank filter with removable basket, all in AISI 304 stainless steel
- ♦ Triple stage dynamic filtration system to separate dirt particles from wash water and to control tank level
- ♦ Electronic control with 3 cycles
- ♦ Automatic start on hood closure
- ♦ Soft start wash pump
- Automatic self-cleaning cycle and shut-off at the end of drain cycle
- ♦ Thermostop system to ensure correct rinse temperature
- Adjustable peristaltic pump for detergent injection
- ♦ Adjustable membrane pump for rinse aid injection
- ♦ Self-diagnostic system with error messages



CWC611D	
basket dimensions (mm)	600X500 or 500X500
tank capacity (litres)	22
boiler heating element (kW)	9.0
electrical connection	400V 3N – 50Hz
total rating (kW)	10.0
dimensions WxDxH (mm)	734x760x1580/2000



