

MXG Series Modular Gourmet Ice Maker – up to 144kg

MXG M 328 AS Medium gourmet cube 20g, Ø30mm x 34mm



Medium gourmet cube
20g, 30mm dia x H 34mm



Note: Ice production rate is measured with the water temperature at 10°C and an ambient temperature of 21°C.

- Up to 144kg daily production rate
- Head only ice maker - requires a separate storage bin to store the ice produced
- Air cooled version
- Produces individual transparent Gourmet crystal clear supercubes
- Horizontal evaporator spray-system technology
- Agion Technology resists the growth of microbes and the development of unpleasant odours
- Simple, reliable electronic controls
- Clean alert indicator to clean filter
- Resistant stainless steel exterior
- Simple, reliable electromechanic controls
- Easy access front condenser air filter
- External indicator lights to show operation status
- Includes removable air filter, water & drain hose


Recommended storage bins

- NB 193 – 129kg storage capacity



MXG Series Modular Gourmet Ice Maker – up to 144kg

MXG M 328 AS



moffat.com.au

Australia
Moffat Pty Limited
Victoria/Tasmania
740 Springvale Road
Mulgrave, Victoria 3170
Telephone 03-9518 3888
Facsimile 03-9518 3833
vsales@moffat.com.au

New South Wales
Telephone 02-8833 4111
nswsales@moffat.com.au

South Australia
Telephone 03-9518 3888
vsales@moffat.com.au

Queensland
Telephone 07-3630 8600
qldsales@moffat.com.au

Western Australia
Telephone 08-9413 2400
wasales@moffat.com.au

Ice production per 24 hours

Ambient temperature / Water temperature

10°C / 10°C	21°C / 10°C	32°C / 21°C
150	144	110

Dimensions

Width:	568mm
Depth:	704mm
Height:	721mm
Nett weight:	66kg
Packed weight:	77kg

Water consumption

Air cooled version: 13.3 litres per hour

Electrical rating

Air cooled version: 230-240V, 1P+N+E, 50Hz, 1200W,
10A cordset supplied

No. Circuit wire:	3
Compressor:	2650W
Energy consumption:	23.3kW/hr

Refrigerant type

R404a

Installation distance from wall

Rear	100mm
Sides	100mm
Operating requirement air temperature 10-43°C	

Water connection requirements

Inlet connection:	3/4"
Cold water:	5-38°C
Pressure:	100-500kPa
Water outlet connection:	Ø3/4"

Important Notice:

Models and specifications are subject to change without notice. This spec sheet is meant for commercial purpose only. For technical documentation please refer to our service manuals.



© Copyright Moffat Ltd
AU.SM.1801