



MX30ATS Reach-in Blast Chiller / Freezer

Standard Features

- Free standing unit on legs
- Ergonomic touch screen controls integrated into the door
- 5 function home screen
- Manual use Soft Chill, Hard Chill, Soft Freeze, Hard Freeze and Self Adaptive I-Chilling
- 99 program cycles
- Favourites key shortcuts to the last 9 programs used
- Pre-chilling cycle key to maximise efficiency
- Multi-point core temperature probe
- Timer mode or continuous run
- Integrated door latch to keep door open when not in use
- Automatic fan stop when opening the door
- Operator selectable de-icing cycle
- External and internal finish made of 304 stainless steel
- Front frame with anti-condensation system
- Injected polyurethane foam insulation 60mm thick




Please refer to Moffat price list for options and accessories

Technical data

Tray capacity	9 x 1/1GN trays
Tray clearance	70mm
External dimensions	W 770mm x D 790mm x H 1565mm
Load capacity	30kg*
Electrical connections	1P+N+E, 230-240V, 50/60Hz, 15A, 1.7kW
Nett weight	140kg
Air-cooled condensing unit - Refrigerant type R452A	
Ambient temperature requirement +15°C — +32°C	

^{*} Note – Load capacities may vary depending on the thermal conductivity of the food being chilled, the thickness of product and container used

Dimensions



(M1) MX30ATS (A) Electrical supply (CU) Useful (MIN) Minimum

Australia moffat.com.au	New Zealand moffat.co.nz
Moffat Pty Limited 740 Springvale Road Mulgrave Victoria 3170 Australia	Moffat Limited 45 Illinois Drive Izone Business Hub Rolleston 7675 New Zealand
Telephone +613-9518 3888 Facsimile +613-9518 3833 vsales@moffat.com.au	Telephone +64 3-983 6600 Facsimile +64 3-983 6660 sales@moffat.co.nz

120 (A) 60 531 (M1) 30 ₹

Disclaimer: All unit capacities are based on subjective testing. Moffat accepts no liability for production values. In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice. © Copyright Moffat Ltd AN-FRI-S-1801



